


TAI AN KOU COSCO 36 Class (K-Class)



Details and Characteristics

Flag: Chinese
Classification: CCS
DP System: DP-2
Speed: 13.5 knots

Propulsion: 2 x 5000 kW, SSP twin azimuth pods

 Bow thrusters:
 2 x 800 kW

 LOA:
 156.0 m (512 ft)

 LBP:
 145.0 m (476 ft)

 Breadth moulded:
 36.0 m (118.1 ft)

 Loaded Draft:
 7.4 m (24.3 ft)

 Deck Submersion:
 9.0 m (29.5 ft)

 Hull Depth:
 10.0 m (32.8 ft)

Cargo Deck: 125 x 36.0 m (410 x 118 ft)

Bulkheads: 5 Transverse bulkheads, Longitudinal bulkheads – 1 at centerline, 2 at 8.80 meters (28.9 ft) and 2 at 16.1

meters (52.8 ft) from centerline

Web frame spacing: Every 2.4 meters (7.9 ft)

Allowable load on maindeck: 18 tons/m²

Casings: 7.6 x 4.95 x 11.8 m (24.9 x 16.2 x 38.7 ft)

Deadweight: 20,131 tons

Ballast System: 4 * 3,215 m3/hr air compressors

44 ballast tanks, including top tanks, double bottom tanks, center tanks and side tanks enabling the vessel to better control motions and accelerations.

Accommodation for 12 persons in addition to crew.

Power Supply to Cargo: 450 V, 60 Hz, 400 kW, 600 A during transit. 380 V, 50 Hz, 250 kW, 400 A during transit.

HOUSTON

24275 Katy Freeway,

Suite 220

Katy, Texas 77494

United States of America

Telephone: +1-281-497-4300

E-mail: commercial@coscoht.com

ROTTERDAM

Montevideo Offices Otto Reuchlinweg 1142 3072 MD Rotterdam The Netherlands

Telephone: +31-10-24 04 777

E-mail: commercial@coscoht.com

GUANGZHOU

Guangzhou Ocean Plaza, 18th Floor

20 Huacheng Avenue

Guangzhou, 510623

P. R. China

E-mail:

semisub.cssc@coscoshipping.com